

重量 (W) の単位 : kg/m

表1 . ボイラ・熱交換器用合金鋼管 (STBA) のサイズ・径・厚さ・重量

外径 D mm	パイプ厚さ (肉厚) : t (mm)																			
	1.2	1.6	2.0	2.3	2.6	2.9	3.2	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0	8.0	9.5	11.0	12.5	
15.9	0.435	0.564	0.686	0.771	0.853	0.930														
19.0		0.687	0.838	0.947	1.05	1.15														
21.7			0.972	1.10	1.22	1.34	1.46													
25.4			1.15	1.31	1.46	1.61	1.75	1.89												
27.2			1.24	1.41	1.58	1.74	1.89	2.05	2.29											
31.8				1.67	1.87	2.07	2.26	2.44	2.74	3.03										
34.0					2.01	2.22	2.43	2.63	2.96	3.27	3.58									
38.1					2.28	2.52	2.75	2.99	3.36	3.73	4.08	4.42								
42.7					2.57	2.85	3.12	3.38	3.82	4.24	4.65	5.05	5.43							
45.0					2.72	3.01	3.30	3.58	4.04	4.49	4.93	5.36	5.77	6.17						
48.6					2.95	3.27	3.58	3.89	4.40	4.89	5.38	5.85	6.30	6.75	7.18					
50.8					3.09	3.43	3.76	4.08	4.62	5.14	5.65	6.14	6.63	7.10	7.56	8.44	9.68	10.8	11.8	
54.0					3.30	3.65	4.01	4.36	4.93	5.49	6.04	6.58	7.10	7.61	8.11	9.07	10.4	11.7	12.8	
57.1						3.88	4.25	4.63	5.24	5.84	6.42	7.00	7.56	8.11	8.65	9.69	11.2	12.5	13.7	
60.3						4.10	4.51	4.90	5.55	6.19	6.82	7.43	8.03	8.62	9.20	10.3	11.9	13.4	14.7	
63.5						4.33	4.76	5.18	5.87	6.55	7.21	7.87	8.51	9.14	9.75	10.9	12.7	14.2	15.7	
65.0						4.44	4.88	5.31	6.02	6.71	7.40	8.07	8.73	9.38	10.0	11.2	13.0	14.6	16.2	
70.0						4.80	5.27	5.74	6.51	7.27	8.01	8.75	9.47	10.2	10.9	12.2	14.2	16.0	17.7	
76.2							5.76	6.27	7.12	7.96	8.78	9.59	10.4	11.2	11.9	13.5	15.6	17.7	19.6	
82.6							6.27	6.83	7.75	8.67	9.57	10.5	11.3	12.2	13.1	14.7	17.1	19.4	21.6	
88.9							6.76	7.37	8.37	9.37	10.3	11.3	12.3	13.2	14.1	16.0	18.6	21.1	23.6	
101.6								8.47	9.63	10.8	11.9	13.0	14.1	15.2	16.3	18.5	21.6	24.6	27.5	
114.3									10.9	12.2	13.5	14.8	16.0	17.3	18.5	21.0	24.6	28.0	31.4	
127.0									12.1	13.6	15.0	16.5	17.9	19.3	20.7	23.5	27.5	31.5	35.3	
139.8													18.2	19.8	21.4	22.9	26.0	30.5	34.9	39.2