

重量(W)の単位: kg/m

表1a. 炭素鋼鋼管(STF410)、合金鋼鋼管(STFA)及びニッケルクロム鉄合金管(NCF-TF)のサイズ・径・厚さ・重量

呼び径		外径 D mm	パイプ厚さ(肉厚): t (mm)																	
B	A		4.0	4.5	5.0	5.5	6.0	6.5	7.0	8.0	9.5	11.0	12.5	14.0	16.0	18.0	20.0	22.0	25.0	28.0
2	50	60.5	5.57	6.21	6.84	7.46	8.06	8.66	9.24	10.4	11.9									
2・1/2	65	76.3		7.97	8.79	9.60	10.4	11.2	12.0	13.5	15.6									
3	80	89.1		9.39	10.4	11.3	12.3	13.2	14.2	16.0	18.6	21.2								
3・1/2	90	101.6		10.8	11.9	13.0	14.1	15.2	16.3	18.5	21.6	24.6	27.5							
4	100	114.3			13.5	14.8	16.0	17.3	18.5	21.0	24.6	28.0	31.4	34.6						
5	125	139.8			16.6	18.2	19.8	21.4	22.9	26.0	30.5	34.9	39.2	43.4	48.8					
6	150	165.2				21.7	23.6	25.4	27.3	31.0	36.5	41.8	47.1	52.2	58.9	65.3				
8	200	216.3						33.6	36.1	41.1	48.4	55.7	62.8	69.8	79.0	88.0	96.8	105		
10	250	267.4						41.8	45.0	51.2	60.4	69.6	78.6	87.5	99.2	111	122	133	149	165