

重量(W)の単位: kg/m

表1b. オーステナイト系ステンレス鋼鋼管(SUS304TF / SUS304HTF / SUS321TF / SUS321HTF)
のサイズ・径・厚さ・重量

| 呼び径 | | 外径 D mm | パイプ厚さ(肉厚): t (mm) | | | | | | | | | | | | | | | | | |
|-------|-----|---------------|-------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| B | A | | 4.0 | 4.5 | 5.0 | 5.5 | 6.0 | 6.5 | 7.0 | 8.0 | 9.5 | 11.0 | 12.5 | 14.0 | 16.0 | 18.0 | 20.0 | 22.0 | 25.0 | 28.0 |
| 2 | 50 | 60.5 | 5.63 | 6.28 | 6.91 | 7.54 | 8.15 | 8.74 | 9.33 | 10.5 | 12.1 | | | | | | | | | |
| 2・1/2 | 65 | 76.3 | | 8.05 | 8.88 | 9.70 | 10.5 | 11.3 | 12.1 | 13.6 | 15.8 | | | | | | | | | |
| 3 | 80 | 89.1 | | 9.48 | 10.5 | 11.5 | 12.4 | 13.4 | 14.3 | 16.2 | 18.8 | 21.4 | | | | | | | | |
| 3・1/2 | 90 | 101.6 | | 10.9 | 12.0 | 13.2 | 14.3 | 15.4 | 16.5 | 18.7 | 21.8 | 24.8 | 27.7 | | | | | | | |
| 4 | 100 | 114.3 | | | 13.6 | 14.9 | 16.2 | 17.5 | 18.7 | 21.2 | 24.8 | 28.3 | 31.7 | 35.0 | | | | | | |
| 5 | 125 | 139.8 | | | 16.8 | 18.4 | 20.0 | 21.6 | 23.2 | 26.3 | 30.8 | 35.3 | 39.6 | 43.9 | 49.3 | | | | | |
| 6 | 150 | 165.2 | | | | 21.9 | 23.8 | 25.7 | 27.6 | 31.3 | 36.8 | 42.3 | 47.5 | 52.7 | 59.5 | 66.0 | | | | |
| 8 | 200 | 216.3 | | | | | | 34.0 | 36.5 | 41.5 | 48.9 | 56.3 | 63.5 | 70.6 | 79.8 | 88.9 | 97.8 | 106 | | |
| 10 | 250 | 267.4 | | | | | | 42.2 | 45.4 | 51.7 | 61.0 | 70.3 | 79.4 | 88.4 | 100 | 112 | 123 | 134 | 151 | 167 |