

重量(W)の単位: kg/m

表1c. オーステナイト系ステンレス鋼鋼管  
(SUS309TF / SUS310TF / SUS316TF / SUS316HTF / SUS347TF / SUS347HTF)のサイズ・径・厚さ・重量

呼び径		外径 D mm	パイプ厚さ(肉厚): t (mm)																	
B	A		4.0	4.5	5.0	5.5	6.0	6.5	7.0	8.0	9.5	11.0	12.5	14.0	16.0	18.0	20.0	22.0	25.0	28.0
2	50	60.5	5.67	6.32	6.96	7.58	8.20	8.80	9.39	10.5	12.1									
2・1/2	65	76.3		8.10	8.94	9.76	10.6	11.4	12.2	13.7	15.9									
3	80	89.1		9.54	10.5	11.5	12.5	13.5	14.4	16.3	19.0	21.5								
3・1/2	90	101.6		11.0	12.1	13.3	14.4	15.5	16.6	18.8	21.9	25.0	27.9							
4	100	114.3			13.7	15.0	16.3	17.6	18.8	21.3	25.0	28.5	31.9	35.2						
5	125	139.8			16.9	18.5	20.1	21.7	23.3	26.4	31.0	35.5	39.9	44.2	49.7					
6	150	165.2				22.0	23.9	25.9	27.8	31.5	37.1	42.5	47.9	53.1	59.8	66.4				
8	200	216.3						34.2	36.7	41.8	49.3	56.6	63.9	71.0	80.3	89.5	98.4	107		
10	250	267.4						42.5	45.7	52.0	61.4	70.7	79.9	88.9	101	113	124	135	152	168