

重量(W)の単位:kg/m

表1d.
SUS430TB,SUS430LXTB,SUS430J1LTB,SUS436LTB 及び SUXM8TB
ステンレス鋼鋼管のサイズ・径・厚さ・重量

外径 D mm	パイプ厚さ(肉厚):t (mm)																			
	1.2	1.6	2.0	2.3	2.6	2.9	3.2	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0	8.0	9.5	11.0	12.5	
15.9	0.427	0.553	0.672	0.757	0.836	0.912														
19.0	0.517	0.673	0.822	0.929	1.03	1.13														
21.7	0.595	0.778	0.953	1.08	1.20	1.32	1.43													
25.4	0.702	0.921	1.13	1.29	1.43	1.58	1.72	1.85												
27.2	0.755	0.991	1.22	1.39	1.55	1.70	1.86	2.01	2.24											
31.8	0.888	1.17	1.44	1.64	1.84	2.03	2.21	2.40	2.69	2.97										
34.0		1.25	1.55	1.76	1.97	2.18	2.38	2.58	2.90	3.21	3.51									
38.1		1.41	1.75	1.99	2.23	2.47	2.70	2.93	3.30	3.66	4.00	4.34								
42.7			1.97	2.25	2.52	2.79	3.06	3.32	3.74	4.16	4.56	4.95	5.33							
45.0			2.08	2.38	2.67	2.95	3.24	3.51	3.97	4.41	4.84	5.26	5.66	6.05						
48.6			2.25	2.58	2.89	3.21	3.51	3.82	4.32	4.80	5.27	5.73	6.18	6.62	7.04					
50.8			2.36	2.70	3.03	3.36	3.68	4.00	4.53	5.04	5.54	6.03	6.50	6.97	7.42	8.28	9.49	10.6	11.6	
54.0			2.52	2.88	3.23	3.58	3.93	4.28	4.84	5.39	5.93	6.45	6.97	7.47	7.96	8.90	10.2	11.4	12.5	
57.1			2.67	3.05	3.43	3.80	4.17	4.54	5.14	5.73	6.30	6.87	7.42	7.96	8.48	9.50	10.9	12.3	13.5	
60.3			2.82	3.23	3.63	4.03	4.42	4.81	5.45	6.07	6.69	7.29	7.88	8.46	9.03	10.1	11.7	13.1	14.5	
63.5				3.40	3.83	4.25	4.67	5.08	5.76	6.42	7.08	7.72	8.35	8.96	9.57	10.7	12.4	14.0	15.4	
65.0				3.49	3.92	4.36	4.78	5.21	5.90	6.59	7.26	7.92	8.56	9.20	9.82	11.0	12.8	14.4	15.9	
70.0				3.77	4.24	4.71	5.17	5.63	6.39	7.13	7.86	8.58	9.29	10.0	10.7	12.0	13.9	15.7	17.4	
76.2				4.11	4.63	5.14	5.65	6.16	6.99	7.80	8.61	9.41	10.2	11.0	11.7	13.2	15.3	17.3	19.3	
82.6							6.15	6.70	7.61	8.50	9.39	10.3	11.1	12.0	12.8	14.4	16.8	19.1	21.2	
88.9							6.63	7.23	8.21	9.19	10.1	11.1	12.0	13.0	13.9	15.7	18.2	20.7	23.1	
101.6								8.31	9.44	10.6	11.7	12.8	13.9	15.0	16.0	18.1	21.2	24.1	26.9	
114.3									10.7	12.0	13.2	14.5	15.7	16.9	18.2	20.6	24.1	27.5	30.8	
127.0									11.9	13.3	14.8	16.2	17.6	18.9	20.3	23.0	27.0	30.9	34.6	
139.8													17.9	19.4	21.0	22.5	25.5	29.9	34.3	38.5