

SGP配管のサイズ・重量・寸法許容差							
呼び径		外径 mm	外形の許容差		厚さ mm	厚さの 許容差	ソケットを含ま ない単位重量 kg/m
			テーパねじ を切る管	それ以外 の管			
B	A						
1/8	6	10.5	± 0.5mm	± 0.5mm	2.0		0.419
1/4	8	13.8	± 0.5mm	± 0.5mm	2.3		0.652
3/8	10	17.3	± 0.5mm	± 0.5mm	2.3		0.851
1/2	15	21.7	± 0.5mm	± 0.5mm	2.8		1.31
3/4	20	27.2	± 0.5mm	± 0.5mm	2.8		1.68
1	25	34.0	± 0.5mm	± 0.5mm	3.2		2.43
1・1/4	32	42.7	± 0.5mm	± 0.5mm	3.5		3.38
1・1/2	40	48.6	± 0.5mm	± 0.5mm	3.5		3.89
2	50	60.5	± 0.5mm	± 1%	3.8		5.31
2・1/2	65	76.3	± 0.7mm	± 1%	4.2		7.47
3	80	89.1	± 0.8mm	± 1%	4.2		8.79
3・1/2	90	101.6	± 0.8mm	± 1%	4.2	+ 規定しない - 12.5%	10.1
4	100	114.3	± 0.8mm	± 1%	4.5		12.2
5	125	139.8	± 0.8mm	± 1%	4.5		15.0
6	150	165.2	± 0.8mm	± 1.6mm	5.0		19.8
7	175	190.7	± 0.9mm	± 1.6mm	5.3		24.2
8	200	216.3	± 1.0mm	± 0.8%	5.8		30.1
9	225	241.8	± 1.2mm	± 0.8%	6.2		36.0
10	250	267.4	± 1.3mm	± 0.8%	6.6		42.4
12	300	318.5	± 1.5mm	± 0.8%	6.9		53.0
14	350	355.6	-	± 0.8%	7.9		67.7
16	400	406.4	-	± 0.8%	7.9		77.6
18	450	457.2	-	± 0.8%	7.9		87.5
20	500	508.0	-	± 0.8%	7.9		97.4