

STPY400配管用アーク溶接炭素鋼鋼管のサイズ・厚さ(肉厚)・重量

呼び径		外径 mm	単位重量 W (kg/m) 厚さ(肉厚) t (mm)															
			4.5	5.0	5.5	6.0	6.4	7.1	7.9	8.7	9.5	10.3	11.1	11.9	12.7	13.1	15.1	15.9
B	A	mm	4.5	5.0	5.5	6.0	6.4	7.1	7.9	8.7	9.5	10.3	11.1	11.9	12.7	13.1	15.1	15.9
14	350	355.6	38.9	43.3	47.5	51.7	55.1	61.0	67.7	74.4	81.1	87.7	94.3	101	107			
16	400	406.4	44.5	49.5	54.2	59.2	63.1	69.9	77.6	85.3	93.0	101	108	116	123			
18	450	457.2	50.2	55.8	61.2	66.8	71.1	78.8	87.5	96.2	105	114	122	131	139			
20	500	508.0	55.9	62.2	68.0	74.3	79.2	87.7	97.4	107	117	126	136	146	155			
22	550	558.8	61.5	68.2	75.2	81.8	87.2	96.6	107	118	129	139	150	160	171			
24	600	609.6	67.1	74.8	82.0	89.3	95.2	105	117	129	141	152	164	175	187			
26	650	660.4		80.8	88.9	96.8	103	114	127	140	152	165	178	190	203			
28	700	711.2		87.1	95.5	104	111	123	137	151	164	178	192	205	219			
30	750	762.0		93.2	102	112	119	132	147	162	176	191	206	220	235			
32	800	812.8		99.5	109	119	127	141	157	173	188	204	219	235	251	258	297	312
34	850	863.6		106	116	127	135	150	167	183	200	217	233	250	266	275	316	332
36	900	914.4		112	124	134	143	159	177	194	212	230	247	265	282	291	335	352
40	1000	1016.0		125	137	149	159	177	196	216	236	255	275	295	314	324	373	392
44	1100	1117.6		137	151	165	175	195	216	240	260	281	303	324	346	357	411	432
48	1200	1219.2		149	165	180	192	212	236	260	283	307	331	354	378	390	448	472
54	1350	1371.6		168	185	202	216	239	266	293	319	345	373	399	426	439	505	532
60	1500	1524.0		187	206	225	240	265	295	325	355	385	413	444	473	488	562	591
64	1600	1625.6		200	220	240	256	284	315	347	380	410	441	474	505	521	600	631
72	1800	1828.8									426	462	498	529	569	587	675	711
80	2000	2032.0															751	791

黄色の網掛け部分はJISに規定されているもの

呼び方 例：600A×6.4 又は 24B×6.4